



Machine Specifications

- Feed Speed 20 - 150 ft/min
Controlled via VFD Drives
- Application Glue Roller
DIA = 150mm
- Doctor Roller DIA = 180mm
- Maximum Coating
Width = 14"
- Maximum Material
Thickness = 4"

Machine Equipped With

- Smooth Chrome Ground-Plated
Doctor Roller
- Silicone Covered Application
Roller
- Teflon Side Dams
- Clean Up Pan for Easy
Cleaning at the End of Shifts
- External Oil Heater

PUR Roll Coaters

An Accurate and Efficient Solution for Application of Hot Melt Glue

The RfsProtech PUR Roll Coater is a heavy duty, 14" Hot Melt Roll Coater designed to apply hot melt glue to the face surface of various substrates. The amount of glue applied to the substrate is controlled by adjusting the distance between the doctor roller and application roller. As the distance is increased, more glue will be applied. The amount of glue dispensed can be controlled to an exact amount. Both the Doctor roller and the Application roller are heated with hot circulating oil.

FEATURES

- Touch Screen HMI
- Quick Change Bearing Block
- Feed Speed Controlled via VFD
- Heated Rollers to Maintain Constant Glue Temperature

BENEFITS

- Minimal Glue Waste
- Applies Precise Coating Amounts
- Quick Change Bearing Block for Easy Roller Replacement



ogden
group

1320 Industrial Drive
Matthews, NC 28105 USA

704-845-2785 • ogden-group.com